

TECHNICAL SPECIFICATIONS - BATH




Tahoe 55 Freestanding


Nominal dimensions: 55" x 31" x 23" [139.7 cm x 78.7 cm x 58.4 cm]

Seats: 1 Product code: **TA55** Draft revision: **2017110309100**

Lumbar support: no Arm rests: no Low-profile available: no

Draft and specs





Additional(s) note(s)

Handmade product, edge width may be uneven and vary. The overflow is factory installed, the drain is included but not installed. When ordered with AeroMassage, blower must be remote mounted. If system, delivered with keypad not installed and remote control is included.

Specifications

Capacity: 47 IMP Gal. / 61.3 US Gal. / 213.6 liters
AeroMassageTM: 40 Easy CleanTM air jets
Super AeroMassageTM: unavailable
Comfort AirTM: unavailable

Series: Authentik Signature

Characteristics: One-piece freestanding bath

Remarks

All measures have a precision of \pm 1/4" (0,63cm) If a measure is present on one side only, part is symmetrical *internal dimensions taken at 4" (10cm) from bath bottom *capacity is measured by filling the bath to 1-1/2" under the overflow

Available models

Soaker ☐
Comfort AirTM ☐
AeroMassageTM ☐
Super AeroMassageTM ☐

Available recommended options


Front skirt:

Recommended drain: Incl. INF101M (White finish)

Tile flanges: unavailable

Floating remote control: included if ordered with system

Linear overflow: Integrated



| Legend | |
|--|-----------------------|
| S Blower | L Chromatherapy light |
| P2) Grab bar | C Keypad |
| Recommended faucets drilling location* | |
| Deck cut-out line | |

Web:

Email:

http://www.oceania-attitude.com

info@bainsoceania.com

*It is possible to install the faucets elsewhere on the product. The installer must verify that there are no piping or wires before drilling.

IMPORTANT NOTE: Specifications, dimensions and models are subject to change.

Visit our website http://www.oceania-attitude.com to access up-to-date dimensions and information. In all cases, information on the website is the most up-to-date.

Phone: 1-877-332-4224

Fax : 1-866-460-4334